

- * Can't use the Flash Editor with the unconfirmed ECU ID.
- * Flash Editor work with stock ECU and normal data only. If the Flash Editor is used with ECU which is already rewritten with other product, it might cause a malfunction.

(2012.11.19)

42015-AM001		42015-AF001		42015-AF002		42015-AF003		
GZ4A		GRF/GVF		GRB/GVB		BR9/BM9		
Confirmed	Version	Confirmed	Version	Confirmed	Version	Confirmed	Version	
52360016	MI0001.102	AZ1G502L	SB0001.100	AZ1G500F	SB0002.103	AE5F300A	SB0003.101	
52360018		AZ1G800F		AZ1G800S		AE5I410A		
52370023		ditto(*1)	SB0001.101	ditto(*1)	SB0002.104	AE51001A	SB0003.103	
52370024		ditto	SB0001.201 (*2)	AZ1G301F	SB0002.105	AE5F300B	SB0003.104	
54550003				AZ1G300F	SB0002.106	AE5K000A	SB0003.201 (*2)	
56180002				ditto	SB0002.201 (*2)	AE5K001B		
56880007	MI0001.104					AE5L131A	SB0003.203	
54560003	MI0001.105			AZ1G800T	SB0002.204	[EyeSight] is not supported.		
56180005	MI0001.201 (*2)			AZ1K000S				
56870004				PowerWriter only: - AZ1G501K (Spec-C) (No data for Phase1, Phase 2 pre-set data)				
56870006								
56880005								
56880009								
54550005								
52360022	MI0001.205							
52370028								
56870008								
Even if you write the Phase 2 data, the power will not go up for 300ps model. Please set it up with Powerwriter.								

*1 Change the display when "MAKE MAP" with unconfirmed ECU ID

*2 Improved check function of saved ECU data: Please use the PowerWriter ver. 1.05 or later if you use the FLASH EDITOR software version *****.200 or later and PowerWriter.

Flash Editor software ver.	PowerWriter ~ ver. 1.04	PowerWriter ver. 1.05~
*****.1**	○	○
*****.2**	×	○

How to check the ECU ID

< For GZ4A >

- 1 Stop engine.
- 2 Connect the Flash Editor OBD II connector to the car.
- 3 Turn on the IG. (not the engine yet)
- 4 Select Editor Status from the Flash Editor menu.
- 5 Check the ID of the "This ECU DATA"
- 6 Turn off the IG.

< For SUBARU >

- 1 Stop engine.
- 2 Connect the Flash Editor OBD II connector to the car.
- 3 Turn on the IG. (not the engine yet)
- 4 Select "ECU READ" from the Flash Editor menu and read normal data.
- 5 Turn off the IG after reading.
- 6 Select Editor Status from the Flash Editor menu.
- 7 Check "int ID" of "SAVE ECU DATA"